

Queue GetOrders

This function sends a signal to the local Pckasse installation at the customers site and tells it to do a getOrders call against the webshop.

<https://min.pckasse.no/QueueGetOrders.aspx?licenceno=x>

x is the Pckasse licence number

It returns the following http status codes

- 200 Signal received, but some of the databases failed.
Check individual status codes in the JSON string returned (see next page)
- 201 All databases with this licence number have received the signal and acted.
- 400 Something wrong with the parameters (Forgot / illegal licence no. etc)
- 500 Server error of some sort
- 502 Bad response from Pckasse
- 503 No response / Pckasse is not started at customers site / server down
- 504 Timeout

Status codes for Individual databases is the same (201 – All good, 200 – Check message)

Actions from caller based on status code

- 201 All good! 😊
- 200 Check OkCount, FailedCount and individual database status codes.
- 4xx Do not try again without fixing your parameters
- 5xx Try again in a little while

Multiple Databases with the same Licence number

Specify Db if you only want to signal a specific database.

<https://min.pckasse.no/QueueGetOrders.aspx?LicenceNo=x&Db=y>

When to call

Do NOT call QueueGetOrders with a timer. (Ex every 15 minutes.)

Call it after the customer has paid and the order is ready to be downloaded

JSON

4xx and 5xx

```
{  
    "error": "Some description"  
}
```

2xx

```
{  
    "OkCount": 0,  
    "FailedCount": 1,  
    "DbResults": [  
        {  
            "LicenceNo": 1000,  
            "Server": "TestServer",  
            "Database": "TestDatabase",  
            "Name": "Demo butikk",  
            "Name2": "",  
            "StatusCode": 200,  
            "Message": "Webshop not activated (DESKTOP-5D26GES, PCKasse, 3.1.5.71)"  
        }  
    ]  
}
```